



Ordering Code:

Part No.	Capacity
	Fx=Fy=Fz
FNZ-10N	10N
FNZ-20N	20N
FNZ-30N	30N
FNZ-50N	50N
FNZ-100N	100N

--- Specifications / 规格参数 ---

Capacity/量程	Fx/Fy/Fz---10/20/30/50/100N		
Rated Output 额定输出	1.0mV/V	Crosstalk 串扰	<2% F.S.
Excitation 激励电压	3~12V	Operating Temp. 工作温度范围	-10...+50°C
Zero Balance 零点输出	±0.1mV/V	Temp. Shift Zero 零点温度漂移	±0.05% of R.O./°C
Nonlinearity 非线性	±0.2% of R.O.	Temp. Shift Span 灵敏度温度漂移	±0.01% of R.O./°C
Hysteresis 滞后	±0.2% of R.O.	Input Resistance 输入阻抗	350±50Ω
Nonrepeatability 非重复性	±0.1% of R.O.	Output Resistance 输出阻抗	350±10Ω
Creep(5min) 蠕变(5min)	±0.1% of R.O.	Insulation Resistance 绝缘阻抗	>2000MΩ(50V)
Safe Overload 安全过载	150% of F.S.	Ingress Protection 防护等级	IP62
Ultimate Overload 极限过载	200% of F.S.	Material of Element 弹性体材料	Aluminum alloy 铝合金
Cable 导线	Ø3*2000mm 4-core shielded cable(Longer cable available) Ø3*2000mm 4芯屏蔽线		
R.O.=Rated Output/额定输出 F.S.=Full Scale/满量程			

• Subject to change without notice / 如有更改,不另行通知