



Capacity/KN	H	A	B	C	D	E	M	SR
2/3/5/7	88	79	52	20	59	30	5	35
10/20/30/50	100	91	68	28	74	38	6	65
70/100	130	120	78	32	86	56	8	85
150/200/300	140	129	78	40	86	56	10	200
400/500/600	150	133	92	80	100	68	12	350
1000	170	156	98	80	107	68	16	500
1500/2000	220	201	148	120	158	100	16	1000

--- Specifications / 规格参数 ---

Capacity/量程	2/3/5/7/10/20/30/50/70/100/150/200/300/400/500/600/1000/1500/2000KN		
Rated Output 额定输出	2.0±10% mV/V	Compensated Temp. 温度补偿范围	-10...+40°C
Excitation 激励电压	5~15V	Operating Temp. 工作温度范围	-20...+60°C
Zero Balance 零点输出	±2% of R.O.	Temp. Shift Zero 零点温度漂移	±0.05% of R.O./10°C
Nonlinearity 非线性	±0.1% of R.O.	Temp. Shift Span 灵敏度温度漂移	±0.05% of R.O./10°C
Hysteresis 滞后	±0.1% of R.O.	Input Resistance 输入阻抗	380±30Ω
Nonrepeatability 非重复性	±0.05% of R.O.	Output Resistance 输出阻抗	350±5Ω
Creep(5min) 蠕变	±0.05% of R.O.	Insulation Resistance 绝缘阻抗	>5000MΩ(50V)
Safe Overload 安全过载	150% of F.S.	Ingress Protection 防护等级	IP65
Ultimate Overload 极限过载	200% of F.S.	Material of Element 弹性体材料	Alloy steel 合金钢
Cable 导线	(<50KN Ø5*3000mm)Ø5.8*6000mm 4-core shielded cable (<50KN Ø5*3000mm)Ø5.8*6000mm 4芯屏蔽线		
R.O.=Rated Output/额定输出 F.S.=Full Scale/满量程			

• Subject to change without notice / 如有更改,不另行通知