



Ordering code

FCMN-500kg - A

Model Capacity Output

- A: 0-5V
- B: 0-10V
- C: 4-20mA

--- Specifications / 规格参数 ---

Capacity/量程	500/ 1000/2000/3000/5000 kg		
Rated Output 额定输出	0-5V, 0-10V 4-20mA	Safe Overload 安全过载	150% of F.S.
Excitation 激励电压	12~24V DC	Ultimate Overload 极限过载	200% of F.S.
Zero Balance 零点输出	±2% of R.O.	Operating Temp. 工作温度范围	-10...+60°C
Nonlinearity 非线性	±0.2% of R.O.	Temp. Shift Zero 零点度温度漂移	±0.01% of R.O./°C
Hysteresis 滞后	±0.2% of R.O.	Temp. Shift Span 灵敏度温度漂移	±0.01% of R.O./°C
Nonrepeatability 非重复性	±0.1% of R.O.	Ingress Protection 防护等级	IP65
Creep(3min) 蠕变(3min)	±0.1% of R.O.	Material of Element 弹性体材料	Stainless steel 不锈钢
Cable & Wiring code	Ø5.3*3000mm Red: Power+ Green: Output+ Black: Power-/Output-		
R.O.=Rated Output/额定输出 F.S.=Full Scale/满量程			

• Subject to change without notice / 如有更改,不另行通知