







Model	M
FSLP-M	M12
FSLP-A	1/2-20 UNF

Ordering code
FSLP-A - 2kN
Model Capacity



Wiring Diagram/接线图



--- Specifications / 规格参数 ---

Capacity/量程	1/2/3/4.5/9 kN		
Rated Output 额定输出	30 mV/V	Compensated Temp. 温度补偿范围	0...+50°C
Excitation 激励电压	3~5V	Operating Temp. 工作温度范围	-20...+70°C
Zero Balance 零点输出	±1 mV/V	Temp. Shift Zero 零点温度漂移	±0.5% of R.O./°C
Nonlinearity 非线性	±0.3% of R.O.	Temp. Shift Span 灵敏度温度漂移	±0.5% of R.O./°C
Hysteresis 滞后	±0.3% of R.O.	Input Resistance 输入阻抗	400±50Ω
Nonrepeatability 非重复性	±0.1% of R.O.	Output Resistance 输出阻抗	350±50Ω
Creep(3min) 蠕变(3min)	±0.2% of R.O.	Insulation Resistance 绝缘阻抗	>2000MΩ(50V)
Safe Overload 安全过载	150% of F.S.	Ingress Protection 防护等级	IP65
Ultimate Overload 极限过载	250% of F.S.	Material of Element 弹性体材料	Stainless steel 不锈钢
Cable 导线	Ø3*3000mm 4-core shielded cable Ø3*3000mm 4芯屏蔽线		
R.O.=Rated Output/额定输出 F.S.=Full Scale/满量程			

• Subject to change without notice / 如有更改,不另行通知