



■ Rotating speed no higher than 2000RPM

--- Specifications / 规格参数 ---

Capacity/量程	10/20/30/50/100/200/300 NM		
Rated Output/额定输出	1.5 mV/V	Compensated Temp./温度补偿范围	-10...+40°C
Excitation/激励电压	5~15V	Operating Temp./工作温度范围	-20...+60°C
Zero Balance/零点输出	±2% of R.O.	Temp. Shift Zero/零点温度漂移	±0.02% of R.O./°C
Nonlinearity/非线性	±0.25% of R.O.	Temp. Shift Span/灵敏度温度漂移	±0.02% of R.O./°C
Hysteresis/滞后	±0.25% of R.O.	Input Resistance/输入阻抗	700±50Ω
Nonrepeatability/非重复性	±0.2% of R.O.	Output Resistance/输出阻抗	700±5Ω
Creep(5min)/蠕变	±0.1% of R.O.	Insulation Resistance/绝缘阻抗	>5000MΩ(50V)
Safe Overload/安全过载	120% of F.S.	Ingress Protection/防护等级	IP50
Ultimate Overload/极限过载	150% of F.S.	Material of Element/弹性体材料	Stainless steel/不锈钢
Cable/导线	Ø5.3*3000mm 4-core shielded cable/4芯屏蔽线		
R.O.=Rated Output/额定输出 F.S.=Full Scale/满量程			

• Subject to change without notice / 如有更改,不另行通知