



Ordering code


FZAD-50N-2-2

Capacity

- Excitation
- 1---3~15V
 - 2---12V DC
 - 3---24V DC

Output

- 1---1.5mV/V
- 2---0-5V output
- 3---0-10V output
- 4---4-20mA output
- 5---2-10mA output



--- Specifications / 规格参数 ---

| Capacity/量程 | 10/20/50/100/200/300/500 N | | |
|--|--|-------------------------------|------------------------|
| Rated Output 额定输出 | 1.5mV/V | Excitation 激励电压 | 3-15V |
| | 0-5V/2-10mA | | 12V DC |
| | 0-5V/0-10V/ 4-20mA | | 24V DC |
| Zero Balance 零点输出 | ±5% of R.O. | Temp. Shift Zero 零点温度漂移 | ±0.03% of R.O./°C |
| Nonlinearity 非线性 | ±0.5% of R.O. | Temp. Shift Span 灵敏度温度漂移 | ±0.02% of R.O./°C |
| Hysteresis 滞后 | ±0.5% of R.O. | Input Resistance 输入阻抗 | 380±30Ω |
| Nonrepeatability 非重复性 | ±0.2% of R.O. | Output Resistance 输出阻抗 | 350±5Ω |
| Creep(5min) 蠕变 | ±0.1% of R.O. | Insulation Resistance 绝缘阻抗 | >2000MΩ(50V) |
| Safe Overload 安全过载 | 120% of F.S. | Ingress Protection 防护等级 | IP50 |
| Operating Temp. 工作温度范围 | -10...+60°C | Material of Element 弹性体材料 | Stainless steel 不锈钢 |
| Cable 导线 | Ø5*2000mm 4-core shielded cable Ø5*2000mm 4芯屏蔽线 | | |
| R.O.=Rated Output/额定输出 F.S.=Full Scale/满量程 | | | |

• Subject to change without notice / 如有更改,不另行通知