



Model	Capacity(kg)	D	H	A	B	C	G	h	K	E	d
FZTK-A	15/25/50	100	36.5	50	30	18	12	14	3	70	6.5
FZTK-B	15/25/50/100	105	36.5	60	40	22	17	16	3	75	6.5
FZTK-C	50/75/100/150	125	47.5	70	45	31	25	18	4	95	6.5
FZTK-D	100/150/200/300	175	65	100	70	44	35	23	4	135	8.5
FZTK-E	300/500/600	225	75	130	82	61	50	23	4	175	10.5
FZTK-F	600/1000	265	80	160	94	80	65	33	4	220	10.5

Ordering code  
**FZTK-B - 50kg**  
 Model Capacity

--- Specifications / 规格参数 ---

Capacity/量程	15/25/50/75/100/150/200/300/500/600/1000 kg		
Rated Output 额定输出	1.5 mV/V	Compensated Temp. 温度补偿范围	0...+40°C
Excitation 激励电压	3~12V	Operating Temp. 工作温度范围	-20...+60°C
Zero Balance 零点输出	±0.03mV/V	Temp. Shift Zero 零点温度漂移	±0.02% of R.O./°C
Nonlinearity 非线性	±0.3% of R.O.	Temp. Shift Span 灵敏度温度漂移	±0.02% of R.O./°C
Hysteresis 滞后	±0.3% of R.O.	Input Resistance 输入阻抗	380±30Ω
Nonrepeatability 非重复性	±0.1% of R.O.	Output Resistance 输出阻抗	352±5Ω
Creep(3min) 蠕变	±0.1% of R.O.	Insulation Resistance 绝缘阻抗	>2000MΩ(50V)
Safe Overload 安全过载	150% of F.S.	Ingress Protection 防护等级	IP50
Ultimate Overload 极限过载	200% of F.S.	Material of Element 弹性体材料	Alloy steel 合金钢
Cable 导线	Ø5.3*3000mm 4-core shielded cable Ø5.3*3000mm 4芯屏蔽线		
R.O.=Rated Output/额定输出 F.S.=Full Scale/满量程			

• Subject to change without notice / 如有更改,不另行通知